



Model 66

Category Benefits

- Food waste is ground into particles and flushed away in seconds
- Clean, hygienic, convenient and simple to use
- Easy method to manage food waste in the home, saving you time and helping to minimise trips to the outside dustbin
- Permanent in-house solution that is compact and sits under the sink without taking up valuable storage
- Easy to install into new or existing kitchens and can be fitted to most sinks
- Environmentally responsible, helping reduce the amount of waste that goes to landfill sites

Features

- 1-stage grind technology
- High-torque Dura-Drive® induction motor
- Built-in air switch in chrome and brushed steel
- 4 Year guarantee
- · Stainless steel grind elements
- · Continuous feed
- Overload protection
- Quick Lock® mounting assembly for faster, easier installation
- Cast lugs
- Removable sound baffle

Sample Specification

Food waste disposer(s) shall be InSinkErator® Model 66 with 1-stage grind technology, .75 hp motor, stainless steel grind elements and built-in air switch with chrome and brushed steel options.

Guarantee: 4 Year parts and service.

The complete InSinkErator guarantee is included in the Care & Use Booklet packed with each unit.


Specifications

Type of Feed Continuous On/Off Control Built-In Air Switch Motor Single Phase Time Rating Intermittent Lubrication Permanently Lubricated Upper & Lower Bearings Shipping Weight (Approx.) Overall Height 318 mm Grind Technology 1-Stage Grind Technology		
Motor Single Phase Time Rating Intermittent Lubrication Permanently Lubricated Upper & Lower Bearings Shipping Weight (Approx.) Overall Height 318 mm Grind Technology 1-Stage Grind	Type of Feed	Continuous
Time Rating Intermittent Lubrication Permanently Lubricated Upper & Lower Bearings Shipping Weight (Approx.) Overall Height 318 mm Grind Technology 1-Stage Grind	On/Off Control	Built-In Air Switch
Lubrication Permanently Lubricated Upper & Lower Bearings Shipping Weight (Approx.) Overall Height Grind Technology 1-Stage Grind	Motor	Single Phase
Lubricated Upper & Lower Bearings Shipping Weight (Approx.) Overall Height 318 mm Grind Technology 1-Stage Grind	Time Rating	Intermittent
(Approx.) Overall Height 318 mm Grind Technology 1-Stage Grind	Lubrication	Lubricated Úpper
Grind Technology 1-Stage Grind		8.2 kg
	Overall Height	318 mm
	Grind Technology	

Grind Chamber Capacity	980 ml
Motor Protection	Manual Reset Overload
Average Water Usage	Approximately 4.0 L per Person per Day
Average Electrical Usage	3-4 KWH per Annum
Drain Connection	1-1/2" (3.81 cm)
Dishwasher Drain Connection	Yes

Volts/Hz	HP	RPM	Average Load
120V, 60 Hz	.75	1725	8.1 A
220-240V, 50 Hz	.75	1425	405 W
220-240V, 60 Hz	.75	1725	405 W

Dimensions (mm)



Model	lel 66		
Α	318	D	185
В	168	Е	131
С	64		

Ո

InSinkErator reserves the right to change product specifications without prior notice. The disposer described in this leaflet is for household use: usage in commercial situations is not covered by warranty.

InSinkErator Division Suite 6, Building 6 Hatters Lane Croxley Green Business Park Watford HERTS WD18 8YH United Kingdom

Sales Tel: (0) 1923 297 880 Service Tel: (0) 800 389 3715 www.insinkerator.co.uk

InSinkErator Division Emerson Electric Co. 4700 21st Street Racine, WI 53406-5093 USA Sales/Service Tel: 262-554-3652

www.insinkerator.com/worldmap.html

Download a QR Reader App to Smartphone



